



POOL SOLUTION SERVICES

Cnr 5th Avenue and 5th Street Linden

www.homesolutionservices.co.za

Leigh Mendes: 083 954 4741;

Stewart Sullivan: 079 695 3808



REPLACING FILTER SAND

- 1 Switch pump off on main power switch – bypassing timer
- 2 Select **closed** position on the filter valve selector
- 3 Remove bolts on the filter lid/hatch with special tool/ spanner (if required)
- 4 Insert bolts back on tank (to avoid misplacing them)
- 5 Block the breather pipe to keep it open and maintain its integrity
- 6 Remove all the old sand by hand
- 7 Inspect the turret, fingers & breather pipe
- 8 Half fill the tank with clean water
- 9 Slowly fill tank with new filter sand to correct tank capacity
- 10 Check level is 100mm from the top of the breather pipe cone
- 11 Wash off the top of the tank and remove bolts
- 12 Remove blockage from the breather pipe and ensure it is clear
- 13 Replace lid, insert bolts and tighten
- 14 Prime the pump (fill trap with water) to ensure impeller chamber is flooded
- 15 Select **backwash** on valve selector and switch the power back on
- 16 Backwash filter and rinse filter sand thoroughly
- 17 Switch filter back on and enjoy your clean pool water

***OR....Simply call us on 083 954 4741 or 079 695 3808
and we will provide the sand and experts to take care of it for you.***